

SAFETY DATA SHEET

Kombinon®120

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

▼Trade name

Kombinon®120

Unique formula identifier (UFI)

EVX1-601Y-000W-2H04

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

PC35 Washing and cleaning products

Restricted to professional users.

Use descriptors (REACH)

Sectors of use	Description
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product category	Description
PC 35	Washing and Cleaning Products (including solvent based products)

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

NCA-Verodan A/S

Industriparken 5

DK-9560 Hadsund

Denmark

Tel.: +45 7027 1630

www.ncaa.dk

E-mail

mail@ncaa.dk

Revision

9/11/2023

SDS Version

2.0

Date of previous version

9/11/2023 (1.0)

1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. Classification of the substance or mixture

Skin Corr. 1; H314, Causes severe skin burns and eye damage.

Eye Dam. 1; H318, Causes serious eye damage.

2.2. Label elements

Hazard pictogram(s)



Signal word Danger

Kombinon®120 Page 1 of 14



Hazard statement(s)

Causes severe skin burns and eye damage. (H314)

Precautionary statement(s)

General

-

Prevention

Do not breathe vapour/mist. (P260)

Wear face protection/protective gloves/protective clothing. (P280)

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . (P303+P361+P353) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

Immediately call a POISON CENTER/doctor. (P310)

Storage

-

Disposal

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

Poly(oxy-1,2-ethanediyl), alpha-tridecyl-omega-hydroxy-, branched

Silicid acid, sodium salt

tetrasodium ethylene diamine tetraacetate

Additional labelling

UFI: EVX1-601Y-000W-2H04

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6 REACH: 01-2119475104-44-0000 Index No.: 603-096-00-8	3-5%	Eye Irrit. 2, H319	[1], [3]
Poly(oxy-1,2-ethanediyl), alpha-tridecyl-omega- hydroxy-, branched	CAS No.: 69011-36-5 EC No.: 500-241-6 REACH: 01-2119976362-32-0001 Index No.:	1-3%	Acute Tox. 4, H302 (ATE: 501.00 mg/kg) Eye Dam. 1, H318 (SCL: 10.00 %) Eye Irrit. 2, H319 (SCL: 5.05 %)	[19]
Silicid acid, sodium salt	CAS No.: 1344-09-8 EC No.: 215-687-4 REACH: 01-2119448725-31-0011 Index No.:	1-3%	Skin Irrit. 2, H315 Eye Dam. 1, H318 (SCL: 10.00 %) STOT SE 3, H335	
tetrasodium ethylene diamine tetraacetate	CAS No.: 64-02-8 EC No.: 200-573-9 REACH: 01-2119486762-27 Index No.: 607-428-00-2	1-3%	Acute Tox. 4, H302 Eye Dam. 1, H318 Acute Tox. 4, H332 STOT RE 2, H373	
Cocoamphoacetat	CAS No.: 68608-65-1 EC No.: REACH: 01-2119487973-19 Index No.:	1-3%	Eye Irrit. 2, H319 (SCL: 16.00 %)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Kombinon®120 Page 2 of 14



Other information

- [1] European occupational exposure limit.
- [3] According to REACH, Annex XVII, the substance is subject to restrictions.
- [19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment.

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eve contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Not applicable.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the chemical emergency services on 72 85 20 00 (24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.



Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep only in original packaging.

Storage temperature

0 - 40°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-(2-butoxyethoxy)ethanol

Long term exposure limit (8 hours) (mg/m³): 68

Long term exposure limit (8 hours) (ppm): 10

Short term exposure limit (15 minutes) (mg/m³): 101

Short term exposure limit (15 minutes) (ppm): 15

Annotations:

E = Substance has an EC limit.

sodium hydroxide

Long term exposure limit (8 hours) (mg/m³): 2

Short term exposure limit (15 minutes) (mg/m³): 2

Annotations:

L = The limit is a ceiling value that at no time may be exceeded.

Statutory order 202 on exposure limits for substances and mixtures (21/02/2023)

DNEL

2-(2-butoxyethoxy)ethanol

Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Inhalation	67.5 mg/m ³
Short term – Local effects - Workers	Inhalation	101.2 mg/m ³
Long term – Systemic effects - General population	Oral	6.25 mg/kg bw/day

Poly(oxy-1,2-ethanediyl), alpha-tridecyl-omega-hydroxy-, branched

Duration:	Route of exposure:	DNEL:
-----------	--------------------	-------

Kombinon®120 Page 4 of 14



Long term – Systemic effects - General population	Dermal	93.8 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	263 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	6.53 mg/m ³
Long term – Systemic effects - Workers	Inhalation	37 mg/m³
Long term – Systemic effects - General population	Oral	2.5 mg/kg bw/day

PNEC

2-(2-butoxyethoxy)ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1.1 mg/L
Freshwater sediment		4.4 mg/kg
Intermittent release (freshwater)		11 mg/L
Marine water		110 μg/L
Marine water sediment		440 μg/kg
Predators		56 mg/kg
Soil		320 μg/kg

Poly(oxy-1,2-ethanediyl), alpha-tridecyl-omega-hydroxy-, branched

1 ory (oxy 172 centarically), alpha enaccy officega fry are	., ,	
Route of exposure:	Duration of Exposure:	PNEC:
Activated Sludge Plant	Single	>10.000 mg/l
Freshwater		4.36 μg/L
Freshwater sediment		119.4 μg/kg
Intermittent release (freshwater)		5.44 μg/L
Intermittent release (marine water)		544 ng/L
Marine water		436 ng/L
Marine water sediment		11.94 μg/kg
Sewage treatment plant		4.35 mg/L
Soil		21.3 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Ensure that eyewash stations and safety showers are located within easy reach.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Wash contaminated clothing before reuse.

Use only CE marked protective equipment.

Respiratory Equipment

Kombinon®120 Page 5 of 14



	Туре	Class	Colour	Standards	
	No special when used as intended.				
Sk	in protection				
	Recommended	Type/Category	Standards		
	No special when used as intended.	-	-		
На	and protection				
	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
	Nitrile	0,3	> 240	EN374-2, EN374-3, EN388	
	Butyl	0.3	> 60	EN374-2, EN374-3, EN388	
	Neoprene (Neoprene)	0.38	> 60	EN374-2, EN374-3, EN388	
Еу	e protection				
	Туре	Standards			
	In the likelihood of direct or incidental exposure, use face	EN166			

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

protection.

Liquid

Colour

Colourless

Odour / Odour threshold

Characteristic

рΗ

13,0

Density (g/cm³)

1.05

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

100

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Kombinon®120 Page 6 of 14





Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to the nature of the product.

Flammability (°C)

Testing not relevant or not possible due to the nature of the product.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to the nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (q/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Thermal decomposition may produce corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance Poly(oxy-1,2-ethanediyl), alpha-tridecyl-omega-hydroxy-, branched

Species: Rat
Route of exposure: Oral
Test: LD50

Result: 500-2000 mg/kg ·

Product/substance Silicid acid, sodium salt

Species: Rat
Route of exposure: Dermal
Test: LD50
Result: > 5000 mg/kg ·

Product/substance Silicid acid, sodium salt

Species: Rat
Route of exposure: Inhalation
Test: LD50

Result: 1152 - 1349 mg/ kg ·

Product/substance tetrasodium ethylene diamine tetraacetate

Species: R

Kombinon®120 Page 7 of 14



Route of exposure: Oral LD50

Result: $> 2000 \text{ mg/kg} \cdot$

Product/substance tetrasodium ethylene diamine tetraacetate

Species: Rat
Route of exposure: Inhalation
Test: LC50

Result: 1000-5000 mg/m3 ·

Product/substance Cocoamphoacetat

Species: Rat Route of exposure: Oral Test: LD50

Result: <5000 mg/kg ·

Product/substance sodium hydroxide

Species: Rabbit
Route of exposure: Dermal
Test: LD50

Result: 1,350 mg/kg ·

Product/substance sodium hydroxide

Species: Rat Route of exposure: Oral Test: LD50

Result: 140-340 mg/kg ·

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Endocrine disrupting properties

Not applicable.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance 2-(2-butoxyethoxy)ethanol

Species: Fish

Kombinon®120 Page 8 of 14



 Duration:
 96 hours

 Test:
 LC50

 Result:
 2500 mg/l⋅

Product/substance 2-(2-butoxyethoxy)ethanol

Species: Daphnia
Duration: 48 hours
Test: EC50
Result: 1000 mg/l·

Product/substance Poly(oxy-1,2-ethanediyl), alpha-tridecyl-omega-hydroxy-, branched

Species: Fish
Duration: 96 hours
Test: LC50
Result: 1-10 mg/l·

Product/substance Poly(oxy-1,2-ethanediyl), alpha-tridecyl-omega-hydroxy-, branched

Species: Algae
Duration: 72 hours
Test: EC50
Result: 1-10 mg/l·

Product/substance Poly(oxy-1,2-ethanediyl), alpha-tridecyl-omega-hydroxy-, branched

Species: Daphnia
Duration: 48 hours
Test: EC50
Result: 1-10 mg/l·

Product/substance Silicid acid, sodium salt

Species: Fish
Duration: 96 hours
Test: LC50
Result: 3185 mg/l·

Product/substance Silicid acid, sodium salt

Species: Daphnia
Duration: 48 hours
Test: EC50
Result: 4857 mgI ·

Product/substance Silicid acid, sodium salt

Species: Algae
Duration: 48 hours
Test: EC0
Result: >1000 mg/l·

Product/substance tetrasodium ethylene diamine tetraacetate

Species: Fish
Duration: 96 hours
Test: LC50
Result: > 100 mg/l⋅

Product/substance tetrasodium ethylene diamine tetraacetate

Species:CrustaceanDuration:48 hoursTest:EC50Result:> 100 mg/l·

Product/substance tetrasodium ethylene diamine tetraacetate

Species: Algae
Duration: 72 hours
Test: EC50
Result: > 100 mg/l⋅

Product/substance Cocoamphoacetat

Kombinon®120 Page 9 of 14



Species: Fish
Duration: 96 hours
Test: LC50
Result: 5,3 mg/l·

Product/substance Cocoamphoacetat

Species: Daphnia
Duration: 96 hours
Test: EC50
Result: 8,9 mg/l·

Product/substance Cocoamphoacetat

Species: Algae
Duration: 72 hours
Test: EC50
Result: 16,9 mg/l·

Product/substance sodium hydroxide

Species: Fish
Duration: 96 hours
Test: LC50
Result: 35 - 189 mg/l·

Product/substance sodium hydroxide Species: Crustacean Duration: 48 hours Test: EC50 Result: 40,4 mg/l·

12.2. Persistence and degradability

Product/substance 2-(2-butoxyethoxy)ethanol

Biodegradable: Yes
Test method: OECD 301 E
Result: >70%

Product/substance Poly(oxy-1,2-ethanediyl), alpha-tridecyl-omega-hydroxy-, branched

Biodegradable: Yes
Test method: OECD 301 E
Result: 90%

Product/substance Siodegradable:

Test method: Result: Silicid acid, sodium salt

Yes

Product/substance Cocoamphoacetat

Biodegradable: Yes
Test method: OECD 301 A
Result: 73%

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

Product/substance 2-(2-butoxyethoxy)ethanol

Test method:

Potential bioaccumulation: No LogPow: 0,5600

BCF: No data available.

Other information:

Product/substance Poly(oxy-1,2-ethanediyl), alpha-tridecyl-omega-hydroxy-, branched

Test method:

Potential bioaccumulation: No LogPow: 2,7700 BCF: 98

Kombinon®120 Page 10 of 14



Other information:

Product/substance

Silicid acid, sodium salt

Test method:

Potential bioaccumulation: No

No data available. LogPow: BCF: No data available.

Other information:

Product/substance

tetrasodium ethylene diamine tetraacetate

Test method:

Potential bioaccumulation: No -13,0000 LogPow:

BCF: No data available.

Other information:

Product/substance

Cocoamphoacetat

Test method:

Potential bioaccumulation: No -1,0000 LogPow:

BCF: No data available.

Other information:

Product/substance

sodium hydroxide

Test method:

Potential bioaccumulation: No LogPow: -3,8800 BCF:

Other information:

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 8 - Corrosive

Dispose of contents/container to an approved waste disposal plant.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

20 01 15* **Alkalines**

Waste group H: Waste with low energy content

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 14.2 UN / ID UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN3266 CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)	Transport hazard class: 8 Label: 8 Classification code: C5	III	No	Limited quantities: 5 L Tunnel restriction

Kombinon®120 Page 11 of 14

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
			8			code: (E) See below for additional information.
IMDG	UN3266	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)	Transport hazard class: 8 Label: 8 Classification code: C5	III	No	Limited quantities: 5 L EmS: F-A S-B See below for additional information.
IATA	UN3266	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)	Transport hazard class: 8 Label: 8 Classification code: C5	III	No	See below for additional information.

^{*} Packing group

Additional information

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

REACH, Annex XVII

 $\hbox{2-(2-but oxyethoxy)ethanol is subject to REACH restrictions, REACH annex XVII (entry 55).}$

Labelling of contents according to Detergents Regulation (EC) No 648/2004

< 5%

- · Amphoteric surfactants
- · EDTA and salts thereof
- · Non-ionic surfactants

Product registration number

Pr. Nr. 2293549

Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Kombinon®120 Page 12 of 14

^{**} Environmental hazards



Sources

The Danish Working Environment Authority's executive order no. 239 of 6 April 2005 on young people's work.

Based on Council Directive 94/33 / EC of 22 June 1994 on the protection of young people at work.

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

1993 Hazardous Substances Law

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H302. Harmful if swallowed.

H315, Causes skin irritation.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H373, May cause damage to organs through prolonged or repeated exposure.

The full text of identified uses as mentioned in section 1

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PC 35 = Washing and Cleaning Products (including solvent based products)

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative



Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the substance/mixture in regard of skin corrosion and serious eye damage is based on the pH-criterion given by Regulation (EC) No. 1272/2008 (CLP).

▼ The safety data sheet is validated by

LEJ

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en